

ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.



DRWARD

996 Industrial Drive Madison, IN 47250

Phone: 800.423.1722 Fax: 812.273.7329





Lit# Forward i10 CUTSHEET.2020.07 ©2020 Vehicle Service GroupSM All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group^{5M}, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.



FEATURES:

Symmetrical column design

Spot-Rite[™] 3-stage front arm design - spot vehicles asymmetrically or symmetrically

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Single point lock release
- Powder coated finish
- Includes adapter • storage bracket
- ALI Certified •

INCLUDES LOW-PROFILE THREADED ADAPTERS AND (4 each) ADAPTER

EXTENSIONS AT 3.5" and 5"



Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.	
SPECIFICATIONS	I10N400MBL/RD*
Capacity	10,000 lbs. (4535kg)
Maximum rise	76 -1/4" (1937mm) w/5" extension
Overall Height	143" (3632mm)
Overall Width	131" or optional 137" (3327mm/4380mm)
Drive through clearance	99" (2515mm) or optional 105" (2667mm)
Overhead switch height	137-5/8" (3496mm)
Front reach (Min/Max)	23" / 44-3/8" (584mm/1127mm)
Rear reach (Min/Max)	36" / 58" (914mm/1473mm)
Min/Max adapter height	3-3/4" (95mm) w/o adapter extension 8-3/4" (222mm) w/ 5" adapter extension
Width inside column	109" or optional 115" (2769mm/2921mm)
Voltage/ Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/60Hz
Ceiling height required	144" (3658mm)
*Lifts available in blue and red	

Specifications subject to change without notice or liability.